

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

ATTACHMENT B

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) An optical phase modulator comprising:
a multilayer stack, comprising a plurality of dielectric layers and having a transmission function related to at least one optical property of the stack, for receiving an optical input signal to be phase modulated; and
phase modulator means for producing a nonmechanical change in the at least one optical property of the stack to provide shifting of the transmission function to produce phase modulation of the optical input signal and to thereby produce a phase modulated output signal;
said multilayer stack being disposed perpendicular to the optical signal to be modulated so that the signal passes serially through each dielectric layer of the plurality of dielectric layers.
2. (Original) A phase modulator according to claim 1 wherein said multilayer stack comprises a bandpass multilayer stack.
3. (Original) A phase modulator according to claim 1 wherein said at least optical property is refractive index, said dielectric layers each have a refractive index value, and said phase modulator means causes a variation in the refractive index of said dielectric layers such as to produce the shift in the transmission function.
4. (Original) A phase modulator according to claim 3 wherein said modulator means decreases the refractive index of said dielectric layers so as to shift the transmission function to shorter wavelengths.

5. (Original) A phase modulator according to claim 4 wherein said dielectric layers comprise GaAs and AlAs layers and said decrease is between 0% and 2.0%.
6. (Original) A phase modulator according to claim 5 wherein said decrease is about 1.3%.
7. (Original) A phase modulator according to claim 1 wherein said dielectric layers comprise both layers having a high index of refraction and layers having a low index of refraction.
8. (Original) A phase modulator according to claim 1 wherein said dielectric layers include alternating GaAs and AlAs layers.
9. (Original) A phase modulator according to claim 8 wherein layers of relatively thin layers of AlAs are inserted within selected layers of GaAs to smooth the transmission function of the stack.
10. (Original) A phase modulator according to claim 8 wherein said layers include a plurality of relatively thick layers of GaAs are interspersed at regular intervals within the stack.
11. (Original) A phase modulator according to claim 1 wherein said modulation means comprises means for optically generating free carriers to provide phase modulation of the optical input signal.
12. (Original) A phase modulator according to claim 3 wherein said modulation means comprises means for optically generating free carriers to provide phase modulation of the optical input signal.

13. (Original) A phase modulator according to claim 1 wherein said modulation means comprises means for externally injecting free carriers to provide phase modulation of the optical input signal.
14. (Original) A phase modulator according to claim 3 wherein said modulation means comprises free carrier injection means for adjusting free carrier flow through the stack so as to vary the refractive index of the layers.
15. (Original) A phase modulator according to claim 3 wherein the layers are doped with a medium exhibiting of a refractive index which varies in a nonlinear manner with optical intensity and said modulator means comprises an optical pump for generating an optical beam which, in combination with the propagating optical input signal, modulates the refractive index of the layers.
16. (Original) A phase modulator according to claim 1 wherein said dielectric layers include GaAs layers, wherein at least one quantum well is created within each GaAs layer and said modulation means comprises means for applying an electric field to the layers of said stack.
17. (Currently Amended) An optical switch comprising:
a multilayer stack, comprising a plurality of dielectric layers and having a transmission function related to at least one optical property of the stack, for receiving an optical input signal to be phase modulated; and
optical switching means for producing a nonmechanical change in said at least one optical property of the stack to provide shifting of the transmission function to a region of high reflectivity;
said multilayer stack being disposed perpendicular to the optical input signal to be phase modulated such that the signal passes serially through each dielectric layer of the plurality of dielectric layers.

18. (Currently Amended) An optical switch according to claim 417 wherein said at least optical property is refractive index, said dielectric layers each have a refractive index value, and said optical switching means causes an increase in the refractive index of said dielectric layers so as to produce a shift in the transmission function to longer wavelengths.

19. (New) An optical phase modulator comprising:

a multilayer stack, comprising a plurality of dielectric layers and having a transmission function related to at least one optical property of the stack, for receiving an optical input signal to be phase modulated; and

phase modulator means for producing a nonmechanical change in the at least one optical property of the stack to provide shifting of the transmission function to produce phase modulation of the optical input signal and to thereby produce a phase modulated output signal,

wherein said at least optical property is refractive index, said dielectric layers each have a refractive index value, and said phase modulator means causes a variation in the refractive index of said dielectric layers such as to produce the shift in the transmission function, and

wherein said modulator means decreases the refractive index of said dielectric layers so as to shift the transmission function to shorter wavelengths.

20. (New) An optical phase modulator comprising:

a multilayer stack, comprising a plurality of dielectric layers and having a transmission function related to at least one optical property of the stack, for receiving an optical input signal to be phase modulated; and

phase modulator means for producing a nonmechanical change in the at least one optical property of the stack to provide shifting of the transmission function to produce phase modulation of the optical input signal and to thereby produce a phase modulated output signal,

wherein said dielectric layers include alternating GaAs and AlAs layers, and

wherein layers of relatively thin layers of AIAs are inserted within selected layers of GaAs to smooth the transmission function of the stack.

21. (New) An optical phase modulator comprising:

a multilayer stack, comprising a plurality of dielectric layers and having a transmission function related to at least one optical property of the stack, for receiving an optical input signal to be phase modulated; and

phase modulator means for producing a nonmechanical change in the at least one optical property of the stack to provide shifting of the transmission function to produce phase modulation of the optical input signal and to thereby produce a phase modulated output signal,

wherein said dielectric layers include alternating GaAs and AIAs layers, and

wherein said layers include a plurality of relatively thick layers of GaAs interspersed at regular intervals within the stack.

22. (New) An optical phase modulator comprising:

a multilayer stack, comprising a plurality of dielectric layers and having a transmission function related to at least one optical property of the stack, for receiving an optical input signal to be phase modulated; and

phase modulator means for producing a nonmechanical change in the at least one optical property of the stack to provide shifting of the transmission function to produce phase modulation of the optical input signal and to thereby produce a phase modulated output signal,

wherein said at least optical property is refractive index, said dielectric layers each have a refractive index value, and said phase modulator means causes a variation in the refractive index of said dielectric layers such as to produce the shift in the transmission function,

wherein said modulation means comprises free carrier injection means for adjusting free carrier flow through the stack so as to vary the refractive index of the layers, and

wherein the layers are doped with a medium exhibiting of a refractive index which varies in a nonlinear manner with optical intensity and said phase modulator means comprises an optical pump for generating an optical beam which, in combination with the propagating optical input signal, modulates the refractive index of the layers.